



Product Service

CERTIFICATE

No. Z2 083334 0054 Rev. 01

Model(s):

1000 V DC system voltage Single Glass modules:
UL-xxxM-72, xxx= 330 to 390 in step of 5;
UL-xxxM-60, xxx= 275 to 325 in step of 5;
UL-xxxM-54, xxx= 245 to 290 in step of 5;

1500 V DC system voltage Single Glass modules:
UL-xxxM-72HV, xxx= 330 to 390 in step of 5;
UL-xxxM-60HV, xxx= 275 to 325 in step of 5;
UL-xxxM-54HV, xxx= 245 to 290 in step of 5;
xxx is standing for rated output power at STC

Parameters:

Construction:	Framed, with Junction box, Cable and Connectors.
Safety Class:	Class II
Maximum System Voltage:	1500 V DC or 1000 V DC
Fire Safety Class:	Class C according to UL 790
Severity of Salt mist test:	Severity 5

Tested according to:

IEC 61215-1(ed.1)
IEC 61215-1-1(ed.1)
IEC 61215-2(ed.1)
IEC 61730-1(ed.2)
IEC 61730-2(ed.2)
IEC 61701(ed.2)

Production Facility(ies):

083334

TUV SUD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD TÜV SÜD
ZERTIFIKAT ♦ CERTIFICATE ♦ 認證證書 ♦ CERTIFICADO ♦ CERTIFICAT